



## Construction fall protection requirements

	Guardrail systems	Safety net systems	Personal fall arrest systems	Covers	Positioning device	Fences	Barricades	Equipment guards	Controlled access zone	Warning line system/guardrail	Warning line/safety net system	Warning line/safety personal fall arrest	Warning line system/safety monitor	Safety monitor	Fall protection plan
Unprotected sides and edges	X	X	X												
Leading edges	X	X	X												X*
Hoist areas	X		X												
Holes	X		X	X											
Formwork/reinforcing steel		X	X		X										
Ramps, runways, other walkways	X														
Excavations	X					X	X								
Excavations (wells, pits, shafts)	X			X		X	X								
Dangerous equipment (less than six feet)	X							X							
Dangerous equipment (above six feet)	X	X	X												
Overhand bricklaying	X	X	X						X						
Overhand bricklaying (reaching 10" below)	X	X	X												
Roofing work (low slope)	X	X	X							X	X	X	X	X**	
Steep roofs	X	X	X												
Precast concrete erection	X	X	X												X*
Residential construction (Group 1, 2, 3 or 4 activity – see residential chart)															X*
Wall openings	X	X	X												
Other walking/working surfaces	X	X	X												

\*Must show infeasibility or greater hazard

\*\*Roof width less than 50 feet

This material can be provided to you in a different format (such as Braille, large print, or audiotape) if you call the MNOSHA Training/Outreach Unit at (651) 284-5050; toll-free 1-877-470-OSHA (1-877-470-6742); or via TTY at (651) 297-4198.

Revised March 2005